

Yamamoto

JAPANESE PRECISION MEETS AMERICAN MUSCLE

10BT

MULTI-PIECE FOLDER

PROUDLY BASED IN BLOOMINGTON, IL, **USA**, YAMAMOTO NORTH AMERICA REPRESENTS THE WORLD'S BEST IN INDUSTRIAL LAUNDRY EQUIPMENT.

BACKED BY AN EXTENSIVE SUPPORT NETWORK, JAPANESE ENGINEERING, AND A 5 YEAR WARRANTY, YOU CAN COUNT ON YAMAMOTO'S SUPERIOR QUALITY.



- UP TO 4 STACKING POSITIONS
- +650 PIECES/HOUR
- UNIQUE IN-FEED METHOD FOR CONTROLLED ENTRY
- BLADE LIFTERS FOR PRECISION FOLDS
- 30 AUTO-SORTING PROGRAMS



TRUSTED FOR
+75 YEARS

WITH YOU FOREVER

YAMAMOTO NORTH AMERICA LLC PO BOX 3264 BLOOMINGTON, IL 61701
WWW.YAMAMOTO-NA.COM - 866.204.0519 - INFO@YAMAMOTO-NA.COM

Machine Size	Width	1850 mm (72.8")	Compressed air ※5	Supply pressure	0.7~1.0 MPa (101.5~145 psi)	
	Depth	3950 mm(155.6")		Rated pressure	0.5 MPa (72.6 psi)	
	Height	1750 mm(68.9")		Maximum consumption	150 NL/min 4.8 cu ft/min	
Dimensions of transportation	Width	1550 mm(61.1")	Usage environment	Temperature of Surrounding	5-40 °C	
	Depth	3400 mm(133.9")		Humidity	30-85 %	
	Height	1750 mm(68.9")		Altitude	The machine should be installed in the altitude which is lower than in 1000m(328 ft)	
Weight		1450 kg(3197 lb)	Stacker (3 places)	A	left	
Power	Electrical phase	3phases		B ※6	left	
	Voltage	AC200/208/220 V		C	rear	
	Frequency	60 Hz		output capacity	S, M	600~650 pcs./h ※7, ※8
	Total motor capacity	1.64 kw		L	550~600 pcs./h ※7, ※8	
	Full load current	12.1 A				
Minimum Supply-Circuit Conductor Ampacity		15 A				
Maximum Rating of The Overcurrent Protective Device		15 A				

- ※5 Compressed air must be processed by the air dryer and supplied to the machine.
- ※6 If the final length is less than 350mm, 2-row stacking is possible.
- ※7 It varies depending on a towel length/fold.
- ※8 Maximum folding output in this manual is a mechanical capacity. The folding output varies depending on operator's capability.

