

WUD60G

COMBO WASHER/DRYER

BUILT TO LAST, DESIGNED FOR PERFORMANCE

YAMAMOTO WASHER/DRYER COMBOS ARE BUILT FOR MAXIMUM RELIABILITY, EFFICIENCY, AND EASE OF USE—HELPING YOU LOWER COSTS, MINIMIZE DOWNTIME, AND EXTEND THE LIFE OF YOUR INVESTMENT. ENGINEERED FOR DECADES OF SERVICE AND EQUIPPED WITH ADVANCED PROTECTIONS THAT REDUCE WEAR, EACH COMPONENT IS DESIGNED WITH YOUR OPERATION IN MIND. FROM OVERSIZED WATER VALVES THAT SHORTEN FILL TIMES AND PREVENT CLOGS, TO A PERMANENTLY FORTIFIED BEARING HOUSING WITH AN AUTOMATIC LUBRICATING SYSTEM, YOU CAN REST ASSURED: YAMAMOTO COMBOS ARE MORE THAN MACHINES—THEY ARE LONG-TERM PARTNERS IN PRODUCTIVITY.

SIMPLE AND INTUITIVE OPERATION BACK BY WARRANTY

A USER-FRIENDLY TOUCHSCREEN SIMPLIFIES TRAINING AND DAILY USE, WHILE GIVING OWNERS REAL-TIME INSIGHTS AND CONTROL FOR SMARTER DECISION-MAKING. BUILT WITH JAPANESE PRECISION AND SUPPORTED BY AN UNMATCHED SERVICE NETWORK, EVERY MACHINE COMES WITH THE INDUSTRY'S STRONGEST 5-YEAR WARRANTY—PROVEN TO DELIVER MORE THAN 50,000 TROUBLE-FREE CYCLES.



6" PROFACE TOUCHSCREEN

- EFFORTLESS TRAINING
- CUSTOMIZABLE PROGRAMS
- REAL-TIME DATA ANALYTICS
- EASY MANUAL OPERATION OPTION FOR DIAGNOSTICS



PERMANENTLY SEALED BEARING

- STANDARD WITH AUTOMATIC OILING SYSTEM
- TRIPLE SEAL DESIGN TO EXTEND LIFESPAN
- ENGINEERED TO WITHSTAND THE HEAVIEST USAGE
- MULTI V-BELT SYSTEM FOR INCREASED SERVICE LIFE



ADJUSTABLE DOOR LOCK/HINGES

- POST & PIN STYLE ELIMINATES SAGGING OVER TIME
- ASSURE SAFE & TIGHT SEAL FOR EVERY CYCLE
- EASILY SERVICEABLE AFTER YEARS OF USE



DUAL SOFT-MOUNT SUSPENSION

- OVERSIZED INDUSTRIAL STRENGTH SHOCKS & SPRINGS
- VIRTUALLY ZERO-IMPACT INSTALLATION
- ELIMINATES THE NEED/COST FOR CONCRETE PADS



SELF-SERVICEABLE DRAIN VALVE

- ELIMINATES UNNECESSARY DOWNTIME
- REDUCES MAINTENANCE EXPENSES
- PREVENTS PRODUCTION DELAYS
- DESIGNED FOR TOOLLESS ACCESS



Yamamoto
NORTH AMERICA






WITH YOU FOREVER

A TRUSTED CHOICE BY PROFESSIONALS IN HOSPITALITY,
HEALTHCARE, ATHLETIC, & COMMERCIAL LAUNDRIES.

FOR +75 YEARS

Model No.		WUD60G	
Capacity(Best Practices)	Washer extractor	27.2 kg	60 lbs
	Tumble dryer	13.6 kg	30 lbs
Drum	Diameter	cp762 mm	cp30.0"
	Depth	600 mm	23.6"
	L/ Cubic Feet	273 L	9.6 cu.ft
Machine Size (Packing Size)	Height	1848(1983)mm	72.8(72.8)"
	Width	1012(1040)mm	40.0(40.9)"
	Depth	1393(1540)mm	54.8(60.6)"
Weight of empty machine (Crated Weight)		890kg(945kg)	1965lbs(2085lbs)
Drum Speed	Washing Speed	20-50 rpm	
	Extraction Speed	100-880 rpm	
G - Force	High Speed	330 G	
Dynamic Loading	Frequency	14.7 Hz	
	Dynamic floor weight	1720 kg/m ²	352.3 lb/ft ²
Power	Electrical Phase, Voltage, Frequency	3-phase, AC208~230V, 60Hz	
	Full load current	17A	
Minimum Supply-Circuit Conductor Ampacity		30A	
Maximum Rating of Supply Circuit Overcurrent Protective Device		30A	
Motor Size	Drum	5HP	
	Fan	1HP	
Heating System		Hot Water Supply	
Heating system of the dryer		Gas	
Cold Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Hot Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Soap Cup Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Water Drain	Connection Port	2-1/2NPT	
Dryer Gas	Supply Port	1/2NPT	
	NATURAL GAS Pressure	1.24kPa-2.61kPa (5W.C-10.5W.C)	
	L.P.GAS Pressure	2.49kPa-3.23kPa(10W.C-13W.C)	
Duct Diameter		cp200	7.87"
Gas Consumption		1.8 m ³ /H	63.57 ft ³ /h
Usage environment	Temperature Of Surrounding	5-45 °C, 41-113 °F	
	Humidity	30-85 %	



WUD60S

COMBO WASHER/DRYER

BUILT TO LAST, DESIGNED FOR PERFORMANCE

YAMAMOTO WASHER/DRYER COMBOS ARE BUILT FOR MAXIMUM RELIABILITY, EFFICIENCY, AND EASE OF USE—HELPING YOU LOWER COSTS, MINIMIZE DOWNTIME, AND EXTEND THE LIFE OF YOUR INVESTMENT. ENGINEERED FOR DECADES OF SERVICE AND EQUIPPED WITH ADVANCED PROTECTIONS THAT REDUCE WEAR, EACH COMPONENT IS DESIGNED WITH YOUR OPERATION IN MIND. FROM OVERSIZED WATER VALVES THAT SHORTEN FILL TIMES AND PREVENT CLOGS, TO A PERMANENTLY FORTIFIED BEARING HOUSING WITH AN AUTOMATIC LUBRICATING SYSTEM, YOU CAN REST ASSURED: YAMAMOTO COMBOS ARE MORE THAN MACHINES—THEY ARE LONG-TERM PARTNERS IN PRODUCTIVITY.

SIMPLE AND INTUITIVE OPERATION BACK BY WARRANTY

A USER-FRIENDLY TOUCHSCREEN SIMPLIFIES TRAINING AND DAILY USE, WHILE GIVING OWNERS REAL-TIME INSIGHTS AND CONTROL FOR SMARTER DECISION-MAKING. BUILT WITH JAPANESE PRECISION AND SUPPORTED BY AN UNMATCHED SERVICE NETWORK, EVERY MACHINE COMES WITH THE INDUSTRY'S STRONGEST 5-YEAR WARRANTY—PROVEN TO DELIVER MORE THAN 50,000 TROUBLE-FREE CYCLES.



6" PROFACE TOUCHSCREEN

- EFFORTLESS TRAINING
- CUSTOMIZABLE PROGRAMS
- REAL-TIME DATA ANALYTICS
- EASY MANUAL OPERATION OPTION FOR DIAGNOSTICS



PERMANENTLY SEALED BEARING

- STANDARD WITH AUTOMATIC OILING SYSTEM
- TRIPLE SEAL DESIGN TO EXTEND LIFESPAN
- ENGINEERED TO WITHSTAND THE HEAVIEST USAGE
- MULTI V-BELT SYSTEM FOR INCREASED SERVICE LIFE



ADJUSTABLE DOOR LOCK/HINGES

- POST & PIN STYLE ELIMINATES SAGGING OVER TIME
- ASSURE SAFE & TIGHT SEAL FOR EVERY CYCLE
- EASILY SERVICEABLE AFTER YEARS OF USE



DUAL SOFT-MOUNT SUSPENSION

- OVERSIZED INDUSTRIAL STRENGTH SHOCKS & SPRINGS
- VIRTUALLY ZERO-IMPACT INSTALLATION
- ELIMINATES THE NEED/COST FOR CONCRETE PADS



SELF-SERVICEABLE DRAIN VALVE

- ELIMINATES UNNECESSARY DOWNTIME
- REDUCES MAINTENANCE EXPENSES
- PREVENTS PRODUCTION DELAYS
- DESIGNED FOR TOOLLESS ACCESS



Yamamoto
NORTH AMERICA



WITH YOU FOREVER

A TRUSTED CHOICE BY PROFESSIONALS IN HOSPITALITY,
HEALTHCARE, ATHLETIC, & COMMERCIAL LAUNDRIES.

FOR +75 YEARS

Model No.		WUD60S	
Capacity(Best Practices)	Washer extractor	27 kg	60lbs
	Tumble dryer	13 kg	30lbs
Drum	Diameter	cp762 mm	cp30.0"
	Depth	600 mm	23.6"
	L/ Cubic Feet	273 L	9.6 cu.ft
Machine Size (Packin g Size)	Height	1848(1983)mm	72.8(72.8)"
	Width	1027(1040)mm	40.1(40.9)"
	Depth	1396(1540)mm	55.0(60.6)"
Weight of empty machine (Crated Weight)		890kg(945kg)	1965lbs(2085lbs)
Drum Speed	Washing Speed	20-50 rpm	
	Extraction Speed	100-880 rpm	
G - Force	High Speed	330 G	
Dynamic Loading	Frequency	14.7 Hz	
	Dynamic floor weight	1720 kg/m ²	352.3 lb/ft ²
Power	Electrical Phase, Voltage, Frequency	3-phase, AC208~230V, 60Hz	
	Full load current	17A	
Minimum Supply-Circuit Conductor Ampacity		30A	
Maximum Rating of Supply Circuit Overcurrent Protective Device		30A	
Motor Size	Drum	5HP	
	Fan	1HP	
Heating System		Hot Water Supply & Steam	
Heating system of the dryer		Steam	
Cold Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3 MPa, 14.5-43.5 psi, 1-3 bar	
Hot Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3 MPa , 14.5-43.5 psi , 1-3 bar	
Soap Cup Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3 MPa, 14.5-43.5 psi, 1-3 bar	
Water Drain	Connection Port	2-1/2NPT	
Heating Steam	Supply Port	1/2NPT	
	Drain Port	3/8NPT	
	Pressure	0.5-0.7 MPa, 72.5-101.5 psi , 5-7 bar	
Dryer Steam	Supply Port	1/2NPT	
	Drain Port	1/2NPT	
	Pressure	0.5-0.7 MPa, 72.5-101.5 psi , 5-7 bar	
Duct Diameter		cp200	7.87"
Steam Consumption		35 kg/H	77 lbs/H
Usage environment	Temperature Of Surrounding	5-45 °C, 41-113 °F	
	Humidity	30-85 %	

